iSBC® 608/618 MODULAR CARDCAGE AND BACKPLANE HARDWARE REFERENCE MANUAL

Order Number: 144261-001



iSBC® 608/618 MODULAR CARDCAGE AND BACKPLANE HARDWARE REFERENCE MANUAL

Order Number: 144261-001

REV.	REVISION HISTORY	PRINT DATE
-001	Original issue	2/82
	- SARICOM CIARRO MARRI	
	Baarespapinaa seleptan	
	EDMS NEWS TRANSPAREN	
	10114484	

Additional copies of this manual or other Intel literature may be obtained from:

Literature Department Intel Corporation 3065 Bowers Avenue Santa Clara, CA 95051

The Information in this document is subject to change without notice.

Intel Corporation makes no warranty of any kind with regard to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Intel Corporation assumes no responsibility for any errors that may appear in this document. Intel Corporation makes no commitment to update nor to keep current the information contained in this document.

Intel Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in an Intel product. No other circuit patent licenses are implied.

Intel software products are copyrighted by and shall remain the property of Intel Corporation. Use, duplication or disclosure is subject to restrictions stated in Intel's software license, or as defined as ASPR 7-104.9(a)(9).

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of Intel Corporation.

The following are trademarks of Intel Corporation and its affiliates and may be used only to identify Intel products:

BXP	Insite	iSBC	Multibus
CREDIT	Intel	iSBX	Multimodule
i	intel	Library Manager	Plug-A-Bubble
ICE	Intelevision	MCS	PROMPT
iCS	Intellec	Megachassis	RMX/80
im	iOSP	Micromainframe	System 2000
iMMX	iRMX	Micromap	UPI

PREFACE

This manual provides general information, specifications, installation instructions and service information for the iSBC 608/618 Modular Cardcage and Backplane. Related information is provided in the following publications, available from the Intel corporate Literature Department in Sunnyvale, California (see page ii for mailing address).

- * Intel Multibus Specification, Order Number 9800683.
- * iSBC Applications Handbook, Order Number 142687.
- * OEM Microcomputer Systems Pocket Reference Guide, Order Number 143925.



TABLE OF CONTENTS

CHAPTE	R		Page
1	GENERAL	INFORMATION	1
	1-1	INTRODUCTION	1
	1-2	DESCRIPTION	2
	1-3	SPECIFICATIONS	2
2	PREPARA	TION FOR USE	5
	2-1	INTRODUCTION	5
	2-2	UNPACKING & INSPECTION	5
	2-3	INSTALLATION CONSIDERATIONS	5
		2-4 Physical Dimensions	5
		2-5 Cooling Requirements	6
		2-6 Power Connections	6
	2-7	MULTIBUS® AND AUXILIARY CONNECTORS	6
	2-8	CHASSIS MOUNTING	6
		2-9 Fan Installation	7
	2-10	STACKING INSTRUCTIONS	10
	2-11	PRIORITY RESOLUTION	12
3	SERVICE	INFORMATION	15
	3-1	INTRODUCTION	15
	3-2	SERVICE AND REPAIR ASSISTANCE	15
	3-3	REPLACEMENT PARTS	16
	3-4	SCHEMATIC DIACRAM	16

TABLE OF CONTENTS (continued)

FIGURES

Figure 1-1	• iSBC® 608 Modular Cardcage/Backplane	1
Figure 2-1		8
Figure 2-2		9
Figure 2-3		11
Figure 2-4	Fan Installition Position	11
Figure 2-5	 Priority Jumper Post Numbering 	13
Figure 3-1		19
Figure 3-2	· iSBC 608/618 Schematic	21
	TABLES	
Table 1-1.	iSBC® 608/618 Specifications	3
Table 2-1.	Compatible Power Connectors	7
Table 2-2.	Auxiliary Connector Sources	7
Table 2-3.	Compatible Fans	10
Table 2-4.	Priority Resolution Jumper Configurations	13
Table 3-1.	Renlacement Parts	17

CHAPTER 1 GENERAL INFORMATION

1-1 INTRODUCTION

The iSBC 608 Modular Cardcage and Backplane is a Multibus compatible, eight-slot board chassis with a fully integrated backplane (Figure 1-1). The iSBC 618 Modular Cardcage and Backplane is the expansion version of the iSBC 608 product. One iSBC 618 cardcage may be stacked on the base iSBC 608 cardcage to form a complete 16 slot Multibus system. Depending on the power requirements for the system, the expansion cardcage may use its own power supply.

This manual provides the information you will need to set up the base cardcage in your system. Stacking instructions are provided for system expansion.




Figure 1-1. iSBC® 608 Modular Cardcage/Backplane

isbc® 608/618 modular cardcage & backplane

1-2 DESCRIPTION

The cardcage and backplane will accommodate up to eight standard iSBC Multibus form factor boards. Two slots provide spacing to accommodate iSBC host boards with iSBX Multimodule boards installed, without slot penalty. All slots are iSBC Multimodule compatible without penalty. Power is routed from the power supply to the backplane with one connector and two screw-lug terminals.

System expansion to 16 slots is easily accomplished by stacking an iSBC 618 cardcage onto an iSBC 608 cardcage. All Multibus lines are routed to the expansion backplane via a single edge connector. Interleaved signal and ground traces are incorporated into the iSBC 608/618 design. This enhancement improves backplane noise immunity and minimizes signal-to-signal coupling.

Each backplane is equipped with a set of jumper connectors for use in establishing board priority. This type of parallel priority scheme is useful in systems which utilize more than one master board. Each of the eight slots can be assigned a priority level with this priority resolution circuitry. Master boards can reside in any slot.

Backplane space is allocated for installing an auxiliary 60-pin connector next to each Multibus connector. The auxiliary connector is typically used for iSBC boards with a functional P2 edge connector. The P2 connector is used on certain single board computers and expansion boards for optional control signals and battery backup provisions.

1-3 SPECIFICATIONS

Cardcage and backplane specifications are provided in Table 1-1.

Table 1-1. iSBC® 608/618 Specifications

Physical Dimensions:	Height: 8.40 inches Width: 13.16 inches Depth: 7.50 inches Weight: 3.50 pounds
Board Slot Spacing:	Top - J1: 1.20 inches (to center) J1 - J2: 1.30 inches (center to center) J2 - J3: 0.80 inches (center to center) J3 - J4: 0.80 inches (center to center) J4 - J5: 0.80 inches (center to center) J5 - J6: 0.80 inches (center to center) J6 - J7: 0.80 inches (center to center) J7 - J8: 0.80 inches (center to center) J8 - Bottom: 0.70 inches (from center)
Electrical Characteristics: (maximum current)	+5V @ 60 A Maximum +12V @ 6 A Maximum -12V @ 2 A Maximum -5V @ 2 A Maximum GND @ 60 A Maximum
Environmental Characteristics:	
Operating Temperature: Storage Temperature: Humidity: Vibration & Shock: Minimum Airflow:	0°C to 55°C -40°C to 85°C 50% to 95% non-condensing @ 25°C to 40°C 2G maximum through 50Hz 200 linear feet/minute

BLANK

CHAPTER 2 PREPARATION FOR USE

2-1 INTRODUCTION

This chapter provides installation instructions and configuration information for the iSBC 608 Modular Cardcage and Backplane. The information presented in this chapter includes unpacking and inspection instructions; installation considerations such as physical dimensions, mounting instructions; connector assignments; and jumper configurations.

2-2 UNPACKING & INSPECTION

Inspect the shipping carton immediately upon receipt for evidence of mishandling during transit. If the shipping carton is severely damaged or waterstained, request that the carrier's agent be present when the carton is opened. If the carrier's agent is not present when the carton is opened and the contents are damaged, keep the carton and packing material for the agent's inspection.

For repairs to a product damaged in shipment contact the Intel Product Service HOTLINE to obtain a return authorization number and further instructions (see section 5-2). A purchase order will be required to complete the repair. A copy of the purchase order should be submitted to the carrier with your claim.

2-3 INSTALLATION CONSIDERATIONS

The iSBC 608 Cardcage can be mounted in either a vertical or horizontal position. It can be used in a chassis or in a standalone configuration. When an iSBC 608 Cardcage is attached to an iSBC 618 Expansion Cardcage the stacked pair may be used with the mounting rails for installation in an EIA compatible (19-inch) rack. The following sections describe important installation considerations.

2-4 Physical Dimensions

Figure 2-1 provides iSBC 608 cardcage physical dimensions. Dimensions of the iSBC 618 cardcage are identical.

2-5 Cooling Requirements

Although the cardcages do not require any cooling, they will require air flow when integrated into a system. A fan mounting bracket is provided with each cardcage for this purpose. Refer to Section 2-9 for fan mounting instructions.

2-6 Power Connections

Three separate power connections are required on the iSBC 608/618 back-plane (base unit): J10, E29, and E30 (refer to figure 2-2). The +5VDC (E29) and GND (E30) connections are 10-24 machine screw terminals which are attached directly to the backplane (see Figure 2-2). Each terminal location is clearly marked on the backplane.

Connections for the ± 12 VDC, ± 12 VDC, and ± 5 VDC are made through receptable J10 on the backplane (see Figure 2-2). Compatible connectors for this plug are listed in Table 2-1.

WARNING

When installing the terminals for +5VDC and GND, ensure each connector is placed correctly. Terminal reversal may cause severe damage to your equipment.

2-7 MULTIBUS® AND AUXILIARY CONNECTORS

The iSBC 608/618 cardcage and backplane is equipped with eight Multibus connectors. These 86-pin connectors allow any iSBC board to be readily installed into the cardcage (pin identification is provided in Figure 3-3).

Adjacent to each 86-pin Multibus connector on the backplane, space is provided for an auxiliary 60-pin connector. Not all iSBC boards require the auxiliary connector, therefore this connector is not supplied with the cardcage. Table 2-2 provides a partial list of vendors who supply compatible auxiliary connectors for iSBC systems. Auxiliary connectors are secured to the backplane with two machine screws.

2-8 CHASSIS MOUNTING

The cardcages may be mounted in a vertical or horizontal position in any chassis which provides adequate ventilation ($<55^{\circ}$ C ambient temperature @ 200 CF/M). Holes are provided on the top and bottom of the cardcage for

mounting purposes (see Figure 2-3). When an iSBC 608 Cardcage is attached to an iSBC 618 Expansion Cardcage the stacked pair may be used with the mounting rails for installation in an EIA compatible (19-inch) rack. See section 2-10 for stacking instructions.

Table 2-1. Compatible Power Connectors

VENDOR	PART NUMBER
3M	3399 - 6026
Ansley	609 - 2600M
Berg	65485 - 009

Table 2-2. Auxiliary Connector Sources

Function	Pins	Centers (inches)	Connector Type	Vendor P/N	
Auxiliary Connector P2	30/60	0.100	Wire Wrap	Elfab BS1020A-30PBB	
12			With 0.128 mounting holes	TI H421121-30 Viking 3KH30/9JNK	
			No Ears	Elfab BW1020D-30PBB	

- Notes: 1. Connector heights are not guaranteed to conform to OEM equipment.
 - 2. Wire wrap pin lengths are not guaranteed to conform to OEM equipment.
 - 3. Connector numbering convention may not agree with board connector.

2-9 Fan Installation

Air circulation must be provided at a minimum flow rate of 200 linear feet/minute through the cardcage. A fan installation bracket is provided with each. Table 2-3 provides a partial list of compatible fans for installation on either the iSBC 608 or iSBC 618 cardcage. Install one or two fans on the mounting bracket, then install the bracket on the cardcage as shown in Figure 2-4.




Figure 2-1. Physical Dimensions (Inches)




Figure 2-2. iSBC® 608/618 Backplane

isbc® 608/618 modular cardcage & backplane

Table 2-3. Compatible Fans

PART NUMBER
SU2A1 - 028267
TA300 - A30473-10
8506D

2-10 STACKING INSTRUCTIONS

The following hardware is required for stacking one iSBC 618 expansion cardcage on an existing iSBC 608 base cardcage (this hardware is included with the iSBC 608 cardcage):

Four 8-32 Screws and Kep Nuts

The following steps outline the stacking procedure:

WARNING

Always remove power from the cardcage and backplane before removing or installing an expansion cardcage. Failure to observe this precaution may result in damage to your equpment and may impose an electrical shock hazard on your personnel.

- a. Remove power from iSBC 608 cardcage (base unit). Unplug power supply from AC outlet if possible.
- b. Remove I/O edge connectors from iSBC boards, and remove all iSBC boards from the cardcage. Make a note of which slot each board occupies (for proper re-installation and priority).
- c. Place the iSBC 618 expansion cardcage on the base unit 'so that the expansion connector interface is properly seated.
- d. Install the four 8-32 screws as shown in Figure 2-3, and tighten.
- e. Remove the jumper between post 23 24 on the iSBC 608 backplane to enable the 16 slot parallel priority resolution.
- f. Reconfigure backplane priority jumpers to obtain desired slot priority order. Refer to Section 2-11 for jumper identification.
- g. Install or move any auxiliary connectors required for your application.
- h. Install rack mount rails, if required. Rails should be installed to the open end of each cardcage.




Figure 2-3. Chassis Mounting/Stacking Holes




Figure 2-4. Fan Installition Position

i. Install iSBC boards into each cardcage. Ensure that board placement conforms to desired priority scheme (see Section 2-11). Install I/O connectors onto edge connectors.

2-11 PRIORITY RESOLUTION

If your system uses more than one Multibus master board, a priority resolution scheme must be established to arbitrate Multibus requests. The iSBC 608 backplane implements a parallel priority resolution scheme by using plug-in jumper connections (Figure 2-5). There are six different priority schemes allowed, each requiring a different jumper configuration. In each configuration, a particular board slot will have a different priority. Table 2-5 lists the priority slots and the corresponding required jumper configuration. The factory default configuration places the highest priority in slot J1, with each successive slot having one level lower priority (see Table 2-5).

In systems where an iSBC 618 expansion cardcage is attached to the base unit, the base unit will have lower priority overall. In this configuration the master boards in the iSBC 608 base cardcage may gain control of the Multibus lines only when no boards in the iSBC 618 cardcage are asserting the Bus Request (BREQ/) signal. Remove jumper connection 23-24 on the iSBC 608 backplane to enable 16 slot resolution.

1 0	8	12 ©	16 •	20	24	26 •	
2	7	11	15 o	19	23 ©	25 •	
3	6	10	14	18	22		
4	5	9	13	17 •	21		

Figure 2-5. Priority Jumper Post Numbering

Table 2-4. Priority Resolution Jumper Configurations

Priority Level/Slot J8 J7 J6 J5 J4 J3 J2 J1								Jumper Connections
J8	J7	J6	J5	J4	J3	J2	J1	Required
7	6	5	4	3	2	1	0	1-2, 3-4, 5-6, 7-8, 9-10, 11-12, 13-14, 15-16, 17-18, 19-20, 21-22, 23-24.*
7	1	5	4	3	2	6	0	1-5, 2-6, 3-7, 4-8, 9-10, 11-12, 13-14, 15-16, 17-18, 19-20, 21-22, 23-24.
0	1	5	4	3	2	6	7	1-5, 2-6, 3-7, 4-8, 9-10, 11-12, 13-17, 14-18, 15-19, 16-20, 21-22, 23-24.
0	6	5	4	3	2	1	7	1-2, 3-4, 5-6, 7-8, 9-10, 11-12, 13-17, 14-18, 15-19, 16-20, 21-22, 23-24.
7	6	5	1	3	2	4	0	1-2, 3-4, 5-9, 6-10, 7-11, 8-12, 13-14, 15-16, 17-18, 19-20, 21-22, 23-24.
7	6	5	0	3	2	1	4	1-2, 3-4, 5-6, 7-8, 9-13, 10-14, 11-15, 12-16, 17-18, 19-20, 21-22, 23-24.

Notes: Priority 0 = Highest; Priority 7 = Lowest.

^{*} Factory Default Configuration

CHAPTER 3 SERVICE INFORMATION

3-1 INTRODUCTION

This chapter provides service assistance information, a schematic diagram of the backplane and a parts list.

3-2 SERVICE AND REPAIR ASSISTANCE

United States Customers can obtain service and repair assistance by contacting the Intel Product Service Hotline in Phoenix, Arizona. (refer to telephone number below.) Customers outside the United States should contact their sales source (Intel Sales Office or Authorized Distributor) for service information and repair assistance.

Before calling the Product Service Hotline, you should have the following information available:

- a. Date you received the product.
- b. Complete part number of the product (including dash number). On boards, this number is usually silk-screened onto the board. On other products, it is usually stamped on a label.
- c. Serial number of product. On boards, this number is usually stamped on the board. On other products, the serial number is usually stamped on a label.
- d. Shipping and billing addresses.
- e. If your Intel product warranty has expired, you must provide a purchase order number for billing purposes.
- f. If you have an extended warranty agreement, be sure to inform the Hotline personnel of this agreement.

Use the following numbers for contacting the Intel Product Service Hotline:

isbc® 608/618 modular cardcage & backplane

TELEPHONE:

All U.S. locations, except Alaska, Arizona, & Hawaii:

(800) 528 - 0595

All other locations: (602) 869 - 4600

TWX NUMBER:

910 - 951 - 1330

Always contact the Product Service Hotline before returning a product to Intel for repair. You will be given a repair authorization number, shipping instructions, and other important information which will help Intel provide you with fast, efficient service. If you are returning the product because of damage sustained during shipment or if the product is out of warranty, a purchase order is required before Intel can initiate the repair.

In preparing the product for shipment to the Repair Center, use the original factory packing material, if possible. If this material is not available, wrap the product in a cushioning material such as Air Cap TH - 240, manufactured by the Sealed Air Corporation, Hawthorne, N.J. Then enclose in a heavy duty corrugated shipping carton, and label "FRAGILE" to ensure careful handling. Ship only to the address specified by Product Service Hotline personnel.

3-3 REPLACEMENT PARTS

Replacement parts for the iSBC 608 and 618 cardcages are listed in Table 3-1. Backplane parts are shown in Figure 3-1.

3-4 SCHEMATIC DIAGRAM

A schematic diagram of the backplane is shown in Figure 3-2.

Table 3-1. Replacement Parts

PART NUMBER	DESCRIPTION	QUANTITY
iSBC 608 Card	dcage:	
143255-003	Cardcage/Backplane Assembly	1
143998-001	Fan Bracket	1
144161-001	EIA Rack Mounting Rail	2
103417-050	Screw, PanHead 8-32 x 0.44	6
143966-001	Mounting Bracket, Cardcage	4
103417-071	Screw, PH, 10-32 x 0.88	6
103444-008	Nut, Kep 8-32	2
iSBC 608 Back	xplane:	
143741-001	PWB, 8-Slot Backplane	1
101762-049	Capacitor 0.luf +80-20%, 50V (C1-4)	4
100632-021	IC, 74S138 (U1)	1
100637-001	IC, 74148 (U2)	1
101655-059	Resistor, 220 ohm, 5%, 1/4W (R6, 11)	2
101655-089	Resistor, 320 ohm, 5%, 1/4W (R2, 8)	2
101656-030	Resistor, 510 ohm, 5%, 1/4W (R10)	1
101655-004	Resistor, 10K ohm, 5%, 1/4W (R1)	1
101655-061	Resistor, 22K ohm, 5%, 1/4W (R7)	1
101655-003	Resistor, 1K ohm, 5%, 1/4W (R5)	1
101736-023	Resistor Pack, 1K ohm, 2% (RP6,7)	2
101736-028	Resistor Pack, 2.2K ohm, 2% (RP2-5)	4
101729-038	Resistor Pack, 10K ohm, 2% (RP1)	1
102247-001	Multibus Connector (J1-8)	8
106891-013	Connector RA 26 Pin (J10)	1
102743-001	Stake Pin (E1-28, J9-1 to J9-10)	38
102480-001	Shorting Plug	13





Figure 3-2. iSBC 608/618 Schematic (Sheet 1)





INTEL CORPORATION, 3065 Bowers Avenue, Santa Clara, California 95051 (408) 987-8080

Printed in U.S.A.